



Nr.inreg.Reg.Com. J40/26395/1992
C.U.I. RO 3003133

IBAN: RO04 RZBR 0000 0600 0480 4537
Banca: Raiffeisen Bank S.M.B.

Tel/Fax : 021.316.3452
Mobil : 0722-214-215
0788-214-215
0763-833-112

ZECOM TRANS s.r.l.

Splaiul Independentei , nr.215 , sector 6 , Bucharest-Romania , 060041

Tabel comparativ dispozitive monitorizare GPS pt. autovehicule

Model dispozitiv	AVL-201	AVL-310	AVL-340	AVI-380	microAVL
					
Caracteristici					
Monitorizare si comenzi SMS	DA	DA	DA	DA	DA
Monitorizare GPRS	DA	DA	DA	DA	DA
Interval monitorizare bazat pe timp	Min.10 sec	Min.10 sec	Min.10 sec	Min.10 sec	Min.10 sec
Interval de monitorizare bazat pe distanta	NU	Min.10 metri	Min.10 metri	Min.10 metri	NU
Interval de monitorizare bazat pe modif. directie	30grade	Min 10grade	Min.10 grade	Min.10 grade	Min.15 grade
Acumulator intern	240mA	850mA	850mA	850mA	320mA
Alerta la deconectare prin	GPRS GPRS+SMS	GPRS+SMS	GPRS+SMS	GPRS+SMS	GPRS+SMS
Autonomie la deconectarea sursei	Cca40min	Cca.8-12 ore	Cca.8-12ore	Cca.8-12ore	Cca.3-4 ore
Alerta la depasirea unei viteze/SMS	NU	DA	DA	DA	DA
Alerta la deconectarea antenei GPS	Nu e cazul	NU	DA	DA	Nu e cazul
Alerta la bruij /lipsa semnal GPS	Soft DA SMS la cerere	Soft DA SMS la cerere	Soft DA SMS la cerere	Soft DA SMS la cerere	Soft DA SMS la cerere
Alerta la stationare/SMS			DA	DA	DA
Alerta la miscare		DA	DA	DA	DA
Memorie interna		DA		DA	DA
Functie buton SOS	DA	DA	DA	DA	DA
Intrari digitale I/O	2 negative 1 pozitiva	3negative 2pozitive	2negative 1pozitiva	3negative 2pozitive	2negative 1pozitiva
Iesiri digitale I/O Imobilizator	1 iesire DA-cheie	5 iesiri DA-cheie	2 iesiri DA-cheie	5 iesiri DA-cheie	1 iesire Cu montaj aux
Intrari analogice		2 intraro 0-6Vcc	2 intraro 0-6Vcc	2 intraro 0-6Vcc	
Antene incorporate	DA	Externe	Externe	Externe	DA
Raportare tensiune acumulator auto	DA		DA	DA	DA
Raportare tensiune acumulator back-up			DA	DA	DA
Alerta descarcare acumulator auto			DA	DA	DA
Alerta descarcare acumulator back-up		DA	DA	DA	DA
Dimensiuni /mm	87x67x21	104 x 83/62 x 24	105 x 86/65 x 26	105 x 86/65 x 26	79.5 x 38.5 x 10.5
Protectie la umiditate	IP-65	5%~95% necond.	5%~95% necond.	5%~95% necond.	IP-40
Temperatura de lucru	-25 la 65 grC	-25 la 65 grC	-25 la 65 grC	-25 la 65 grC	-25 la 65 grC
PRET in EUR fara TVA Cu monitorizare inclusa 1 an/ FuratTrack	79	129	89	139	89